

Application



Base Stations
Telecommunications



Solar&Wind
Energy Storage



UPS



Data Center



Electric Power
Systems



All-purpose

Technical Specification

Battery Model	MTS25.6-100	MTS25.6-200	MTS51.2-100	MTS51.2-200	MTS51.2-280
Rated Voltage	25.6V	25.6V	51.2V	51.2V	51.2V
Rated Capacity	100Ah	200Ah	100Ah	200Ah	280Ah
Discharge Current	100A	100A	100A	200A	200A
Peak Discharge Current	300A	300A	300A	300A	300A
Cut off Discharge Voltage	22.4V	22.4V	44.8V	44.8V	44.8V
Charge Voltage	29.2V	29.2V	58.4V	58.4V	58.4V
Charge Current	20A	40A	20A	40A	56A
Weight (KG)	24.00	46.50	46.50	83.00	115.00
Dimension (L*W*H)mm	380*240*190	370*160*600	370*160*600	500*160*850	460*260*780

*The MTS series range includes but is not limited to the above models! Please contact us for more information



Guangzhou Marste new energy co., LTD

Website: www.marstepower.com

E-mail: admin@marstepower.com

202, Building A, Cloud Cube Creative Park, Jiahe Street, Baiyun District, Guangzhou City, Guangdong Province, China