

**MT-1.5KW****MT-3KW**

PV(Dc Input)	Recommended max.PV input power	650W	1500W
	Max.input voltage(Voc)	130V	145V
	MPPT operating voltage range	15V-120V (@30V start up)	30V-120V (@30V start up)
	Number of MPPT	1	1
	Max. number of input strings per MPPT	1	1
	Max. input current per MPPT	20A	25A
	Max.short-circuit current per MPPT	25A	27A
Grid(AC Input)	Max input power	2300W	4000W
	Max input current	10A	17.4A
	Rated grid voltage	220/230/240Vac(L,N,PE)	220/230/240Vac(L,N,PE)
	Rated grid frequency	50/60Hz	50/60Hz
	Acceptable range	170-280Vac (For UPS): 90-280Vac (For Home Appliances)	170-280Vac (For UPS): 90-280Vac (For Home Appliances)
Battery parameters (Bidirection)	Battery type	LiFePO4/Lead-acid	LiFePO4/Lead-acid
	Battery voltage range	10~14.5V	20-30V
	Rate Battery Voltage	12Vdc	24Vdc
	Max.charge/discharge current	100A/150A	120A/180A
Back-up Output (AC Output)	Rated output power	1500W/1500VA	3000W/3000VA
	Rated output current	7.8A	15.6A
	Rate Battery Voltage	220/230/240Vac(L,N,PE)	220/230/240Vac(L,N,PE)
	Frequency	50/60Hz	50/60Hz
	Surge power	3600VA 2s	7200VA 2s
	THDv (@ linear load)	<3%	<3%
	Switching time	10ms typical (For UPS) 20ms typical(For Home Appliances)	
Efficiency	Peak efficiency	95%	95%
	Max.MPPT efficiency	93%	92%
Protection	Inner protection	√ Output short-circuit protection √ Output overvoltage protection	
	Surge protection	PV: Type III, AC: Type III	
	IP rating	IP21	
General Parameters	Operating temperature range	-10°C~50°C	
	Relative humidity range	5%-95%	5%-95%
	Max. operating altitude	>2000m derating	>2000m derating
	Standby self-consumption	<10W	<10W
	Installation type	Wall-mounted	Wall-mounted
	Cooling mode	Fan cooling	Fan cooling
	communication	RS232	RS232/RS485
	Display	LCD	LCD
Mechanical Specifications	Inverter dimensions (L*W*H)(mm)	350*290*105	350*290*105
	Net weight (kg)	5.55	6
	Carton dimensions (L*W*H)(mm)	495*385*165	495*385*165
	Gross weight (kg)	6.5	7
	Warranty Period	2 Years	